



IP65

ip65











4.0" color screen





1.5m drop











bluetooth





N5S Minke mobile computers







camera

4000 mah

Features

Scan with speed and comfort.

With the N5S Minke in hand, you can capture practically any type of data, from barcodes to NFC. Its megapixel barcode scanning engine is placed at an angle that allows you to scan comfortably, without needing to tilt the screen. The resulting minimal strain allows you to scan comfortably all day long.

Advanced capacitive touch screen.

The 4.0" HD multi-touch capacitive touch screen dynamically adjusts to the current environment. This enables it to work with or without gloves, wet or dry, and with your fingertip or a stylus.

The best in ergonomics.

Engineered to perfect the user experience, the N5S Minke combines great ergonomics and an intuitive keyboard for comfortable all-day scanning. It's a slim and modern device that is easy to hold in one hand. Protruding and easy-to-use keys leave next to no room for error or confusion.

Long-lasting battery life.

The 4000mAh removable battery combined with the latest dynamic power management technology comfortably guarantees a full shift of continuous use.

Built to survive.

Constructed in robust IP65-rated housing, this device was built to survive in a variety of conditions. It is dust-proof and can be used in a wet environment, while also being resistant to drops of up to 1.5m. The result is a mobile computer that promises years of fuss-free operation.



Application Scenarios



food traceability



inventory



logistics





warehousing

N5S Minke technical specifications

Performance Processor Android 7.0 Processor Quad-core 1.45GHz Memory RAM (Memory RAM) 2GB Memory Flash (Max.) Micro 5D card slot (max. 32GB) Data capture 1D Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. 2D QR Code, PDF417, Data Matrix, MaxiCode, ect. Physical Dimensions (mm) 172 x 72 x 24.8mm Weight 330g (including battery) Display 4*, WVGA (800×480) Touch panel Capacitive touch screen Keypad 28 keys (side keys included) Interfaces Micro USB 2.0 Battery Type 4000 mAh Expected Battery Life Standby; 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 5V2A Audio Microphone / speaker Audio Microphone / speaker Audio ack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Strong Temperature -20°C to 55°C (4°F to 131°F) Stroage Temperature -20°C to 55°C (4°F to 131°F) Humidity	
Memory RAM	
Memory Flash Memory Storage Expansion (Max) 16GB Micro Storage Expansion (Max) Micro SD card slot (max. 32GB) Data Capture 2D TD Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. Physical Ph	
Data capture 1D Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. Physical 10 Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. Physical Microsins (mm) 172 x 72 x 24.8 mm Weight 303g (including battery) Display 4", WVGA (800×480) Touch panel Capacitive touch screen Keypad 28 keys (side keys included) Interfaces Micro USB 2.0 Battery Type 4000 mAh Expected Battery Life 5 tandby. 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 4 hours Audio Microphone/ speaker Audio Ack 3.5mm Audio Jack Expansion Slot Microphone/ speaker Audio Individual Scharge 50 Cet of to 5°C (-4°F to 131°F) Storage Temperature 20°C to 55°C (-4°F to 131°F) Evert Static Discharge (ESD) 412 Key (air discharge), 28 KV (direct discharge) Electro Static Discharge (ESD) 412 Key (air discharge), 28 KV (direct discharge) Electro Static Discharge (SD) 42 Key (air discharge), 28 KV (direct di	
Data capture 1D Code 39, Codabar, Code 128, Interleaved 2 of 5, UPC, EAN, MSI, ect. 2D QR Code, PDF417, Data Matrix, MaxlCode, ect. Physical Dimensions (mm) 172 x 72 x 24.8mm Weight 330g (including battery) Display 4°, WVGA (800×480) Touch panel Capacitive touch screen Keypad 28 keys (side keys included) Interfaces Micro USB 2.0 Battery Type 4000 mAh Expected Battery Life Standby: 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 5V,2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Pop 1.5m Sealing 1P65 WWAN Radio SWAN Radio SC GSM	
Physical Dimensions (mm) 172 x 72 x 24.8mm 172 x 72 x 22 x 22 x 22 x 22 x 22 x 22	
Physical Physical Project Project Project Project Physical P	
Weight 330g (including battery)	
Display	
Touch panel Capacitive touch screen Keypad 28 keys (side keys included) Interfaces Micro USB 2.0 Battery Type 4000 mAh Expected Battery Life Standby: 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 5V,2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Storage Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop Sealing 1P65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD	
Keypad	
Interfaces	
Battery Type 4000 mAh Expected Battery Life 5tandby: 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 5V,2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Expected Battery Life Standby: 500 hours; Scanning: 11 hours of continuous operation Expected Charge Time 4 hours Input Voltage 5V.2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Expected Charge Time 4 hours Input Voltage 5V,2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Storage Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Topo 1.5m Sealing IP65 WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Input Voltage 5V,2A Audio Microphone / speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Storage Temperature -20°C to 55°C (-4°F to 131°F) -5 torage Temperature -30°C to 70°C (-22°F to 158°F) -1 Humidity 5% to 95% (non-condensing) -1 Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) -1 Forp 1.5m -5 sealing 1P65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Audio Microphone/speaker Audio Jack 3.5mm Audio jack Expansion Slot Micro SD card (max. 32GB) Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Toro 1.5m Sealing IP65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Audio Jack 3.5mm Audio Jack Micro SD card (max. 32GB) Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing 1P65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Environmental Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing 1P65 WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 38/39/40/41)	
Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4/21)	
Humidity 5% to 95% (non-condensing) Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4/21)	
Electro Static Discharge (ESD) ±12 kV (air discharge), ±8 kV (direct discharge) Drop 1.5m Sealing IP65 Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4/20), LTE TDD (B	
Drop Sealing 1.5m Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BCO), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4) 49/1	
Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BC0), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4/20)	
Wireless WWAN Radio 2G: GSM (Band 3/8) 3G: WCDMA (Band 1/8), CDMA1X, EVDO (Band BC0), TD-SCDMA (Band 34/39) 4G: LTE FDD (Band 1/3/7/20), LTE TDD (Band 3/4) 38/39/40/41	
38/39/40/41	
WLAN Radio 802.11 a/b/g/n, 2.4 GHz and 5GHz	
WPAN Radio Bluetooth 4.0, 3.0+HS, 2.1+EDR	
RFID 13.56MHz RFID, ISO14443A/B, ISO15693, ISO18000-3, Mifare, FeliCa, RF, Kovio, NFC Forum, Type 1-4 Tag	
GPS High precision GPD+AGPS/Beidou System/ GLONASS	
Accessories Optional Charging cradle	
Standard Battery, AC adapter, USB cable	
Device Management Buckets (MDM), StayLinked (TE)	
Certifications Certifications CTA, SRRC, CCC, CE-RED, RoHS, NCC, BSMI, MTBF, IEC2/FDAII, IEC60825-/EN60825-1	
Warranty Warranty 2 years	



newland-id.com